

5 band HF Yagi - XR5 multi-band HF Yagi antenna



Sales price £1,295.00

Sales price without tax £1,079.17
Tax amount £215.83

An 9 element 5 band HF Yagi (20/17/15/12/10) with 3.2m boom

Description

COMPACT VERSION OF THIS ANTENNA XR5C MkII with CAPACITY LOADED 20M ELEMENTS ONLY 8.9M WIDE! [HERE!](#)

Review by QST magazine on our US version can be found [HERE](#)

The XR5 MkII - A 9 element multi-Band HF 5 Band Super-compact Yagi covering 20m/17m/15m/12m/10m bands with a single feed point

The XR5 has been reduced by more than 30% in length while giving the same performance, 5 HF bands consisting of 20/17/15/12/10 as previous versions. The XR5, comes with a capacity loaded 20m element Option (XR5C which reduces the longest element from 11.6m to 8.9m) and reduced turning radius too! The XR5 is set to become a market-leader very quickly, why not get ahead of the pack with this one and place your order early!

The XR5 MkII - The InnovAntennas XR5C - An 9 element multi-band HF Super-compact Yagi covering 20m/17m/15m/12m/10m bands with a single feed point.

Unique in the Market

The XR5 has the 5 HF bands of 20/17/15/12/10 to match today's HF rigs and give excellent performance on all bands. with a boom of just 3.5m and weighing under 30 Kilos, this antenna has created its own place in the 'full size' HF Beam market.

Unlimited Power Handling

The XR5 has no matching devices, no traps, no coils, no hairpins so nothing to lose valueable power and thus, nothing to over-heat through these inefficient devices. This means the only power limitation you have is how much power your coax cable can handle.

The Ideal partner for SDR Radios

The XR5 is an ideal partner for today's top SDR radios. There is no limitation in how many bands you can monitor or use at once. This means with products such as the Flex 6700, all 5 bands can be monitored at the same time **WITHOUT COMPROMISE.**

Improved Performance

The XR5 MKII has been in development for the last 12 months improving bandwidth and gain to ensure more of each band than ever before can be used without the requirement of an ATU.

Multi-band, Performance-Busting Design

The more bands there are added to a multi-band Yagi, the more interlaced elements there are and in turn, performance per band drops with each no band added. The Unique design of the XR5 MkII means no more than 3 band are interlaced on any part of the boom.

Increased Rigidity

We have modified the construction of the XR5 to provide a more rigid look with faster taper to ensure fatigue due to vortex shedding (constant wind flow causing vibration) are not an issue. 20m element start at 35mm diameter and boom is 50mm diameter.

Excellent All-Weather handling and reliability

With no moving parts and being modelled for wide bandwidth per band, the XR5 MkII is very forgiving in all weathers allowing you to enjoy your

5 band HF Yagi - XR5 multi-band HF Yagi antenna

hobby whatever the location or time of year.

Maintenance Free

Icom North America and **Kenwood UK** changed their HF antennas to 'XR's' to ensure reliability and remove the need for maintenance. If you don't want to be climbing the tower each year to fix stuff, the XR5 MkII is for you.

The Right Materials for the Job

The XR5 standing on it's own in terms of quality. built using the latest CNC technology, all components are at the top of their field too. Our insulators are UV protected and handle -170 to +240 degrees C, our hardware is Marine Grade Stainless Steel and our aluminium aerospace grade T6 6066/6082.



The XR5 has low visual impact and is a low profile design



The XR5 installed at club station G8VGG

Technical Specifications:

Power Rating: 10kw

Boom Length: 3.3 Metres

Weight: 33Kg

Turning Radius: 5.83 Metres

Wind Loading: 1.156 Square Metres

Wind Survival: 185KPH / 115MPH

Other options available if higher wind loading/survival is required.

Stacking Distance: 7 - 12m (11m recommended)

Average Gain per band @ 20m above average ground: 11.24dBi

Specifications - boom and elements

The boom is made from 50mm diameter square tube with a wall thickness of 2mm and thus is super-rigid. The largest diameter elements are the 20m elements with centre sections 35mm in diameter with 2mm wall.

//