

3 element Marine Band OWL Yagi



Budget 3el Marine Band Yagi built with high Quality Components

Rating: Not Rated Yet

Price

Sales price £129.95

Sales price without tax £108.29

[Ask a question about this product](#)

Manufacturer [InnovAntennas](#)

Description



A 3 element low-noise, Marine Band (155MHz - 157MHz) OWL Yagi - For Commercial, Professional and Marine applications

The G0KSC [OWL Yagi](#) (Optimised Wideband Low Impedance) loss-less high gain directional vertical antenna. This compact 3 element OWL provides stunning performance across the Marine band of frequencies (other custom frequency versions are available). Hard to beat with a direct 50 Ohm feed point and no matching losses.

The OWL is capable of wide band operation without performance compromise and unlike other commercial antennas, ours are all [individually computer optimised](#) for their specific frequency of operation . Designed with the very latest modeling software packages costing 10's of thousands of pounds, **Accuracy** and performance assured.

Marine Construction - Built to last

Our antennas are constructed with the best quality materials in order that the best mechanical construction can be achieved, not the cheapest and most profitable! Even a digital caliper is used (with an accuracy of .01mm) to measure the elements during production to ensure they are within 0.2mm of what they should be, this ensures performance is delivered.

- Marine grade Stainless Steel Fittings
- Original Stauff Insulation clamps
- Mill finished boom and elements for highest levels of accuracy
- Quality N-type termination
- Liquid Rubber sealant provided with this antenna to perfectly seal every joint before installation

"Hi,

Just to let you know that we got the antenna installed yesterday (finally!). We installed it on a 5m long 2" diameter pole without any issues. There is movement in the strong winds we had yesterday but nothing excessive.

Initial results are very good with the maximum range being approximately 50% greater than with the existing arrangement, typically about 75km with the maximum recorded so far being 95km. This is with the antenna about 35m above sea level.

I'll let you know the results when I've been able to do some more thorough testing.

Best Regards,

Guy - Sea Reach Systems"

"The Yagi-antenna is very good performance.

I did tuning very careful;

SWR=1.0 with short (30cm) test cable including 2 turns choke balun. SWR=1.1 with 20m actual cable including the balun.

Thank you very much for your support and provided good antennas. JSAF is very happy and expecting good antenna network (100nm reception so far)

I will report you later more detail performance.

Have a nice days!

Taro Yoshikawa - Vesseltracker Japan"

For more information This email address is being protected from spambots. You need JavaScript enabled to view it.
document.getElementById('cloakd53c180c582739c4d31658c5b91f9da3').innerHTML = ""; var prefix = 'ma' + 'il' + 'to'; var path = 'hr' + 'ef' + '=';
var addyd53c180c582739c4d31658c5b91f9da3 = 'justin' + '@'; addyd53c180c582739c4d31658c5b91f9da3 =
addyd53c180c582739c4d31658c5b91f9da3 + 'g0ksc' + '.' + 'co' + '.' + 'uk?subject=4el 2m Antenna question'; var
addy_textd53c180c582739c4d31658c5b91f9da3 = 'Email
here';document.getElementById('cloakd53c180c582739c4d31658c5b91f9da3').innerHTML +=
["+addy_textd53c180c582739c4d31658c5b91f9da3+"](#);

Performance

Gain: 7.04dBi Typical

F/B: 19.23dB Typical

Peak Gain: 7.1dBi

Gain 10m above ground: 12.66dBi

Peak F/B: 25.56dB

Power Rating: 5kw

SWR: Below 1.6:1 from 155.0MHz to 157.5MHz

Boom Length: 60cms

Vertical Stacking: 1m apart (3' 3")

Safe Wind Speed: 150MPH+/242KPH

Specification

This antenna is made with a 1/2" inch (12.7mm) parasitic elements complemented by a driven element of 1/2 inch (12.7mm) and 3/8 inch (9.525mm) diameter tube. It also has fully insulated elements which will ensure continuous, high performance and ensures corrosion will not impact performance. Marine grade stainless steel is used throughout. N-type coaxial termination is provided on this antenna along with a UV resistant Rubber paint (including applicator) in order to ensure all open connections can be thoroughly sealed before final installation. The boom is 3/4" inch square 16SWG aluminium to ensure strength and rigidity and has a **safe wind speed handling of well over 100MPH.**

No figures are made up here as they are in some Ham Radio adverts, all performance figures are verified in the very latest software simulation packages with some antennas being professionally confirmed on an antenna range.

!! The antenna is supplied with a choke balun and liquid rubber sealant for securing and sealing joins !!

Manufactured the right way, not the cheapest way!

Trade Enquiries Welcome