

#### Sales price £219.95

Sales price without tax £183.29 Tax amount £36.66

A Wideband 70MHz OP-DES Yagi



# **Description**

A 6 element wideband 69.90-70.90MHz OP-DES (Opposing Phase Driven Element System) Yagi - Second Generation OP-DES Yagi!

The OP-DES is the newest in patent technology produced by InnovAntennas and is specifically designed for maximum performance, wide-band applications. Read more about the <a href="OP-DES Yagi Here">OP-DES Yagi Here</a>. InnovAntennas use the latest in <a href="Electromagnetic Design Technology">Electromagnetic Design Technology</a> to ensure the very best results and the OP-DES Yagi is proof of that!

This antenna has a flat SWR curve covering 69.90-70.90MHz at 1.1:1 SWR. This compact 6el is a small antenna with a huge punch, Take a look!

### Performance

Gain: 11.07dBi @ 70.200MHz

**F/B:** 31.88dB @ 70.200MHz

Peak Gain: 11.11dBi

Gain at 10m above Ground: 16.73dBi

Peak F/B: 32.43dB

Power Rating: 5kw

SWR: Below 1.1:1 from 69.900MHz to 70.900MHz

Stacking Distance: 2.9-4.0m ( 3.6m recommended)

2 Stacked Gain @ 3.6m spacing: 13.96dBi

2 Stacked F/B: 37.17dB

2 Stacked Gain @ 3.6m Spacing 10m above ground: 19.45dBi

Boom Length: 3.390m

Weight: 4.5Kg / 9.9LB

Turning Radius: 2.269m / 7.22ft

Wind Loading: 0.12 Square Metres / 1.25 Square feet

1 / 3

Wind Survival: 209KPH / 130MPH

Other options available if higher wind loading/survival is required.

#### Specification

This antenna is made with 1/2 inch (12.7mm) centre elements and 3/8 inch (9.525mm) outer elements with the OP-DES end sections 3/8 inch (9.525mm). The antenna has fully insulated elements which will ensure continuous, high performance for many years to come. Boom to mast brackets are included with all antennas which will support 2 inch (50mm) masts. Boom is 1.25 inch (32mm) square 16SWG aluminum.

## OTHER TAPER SCHEDULES ARE AVAILABLE FOR THIS ANTENNA, CALL OR EMAIL FOR DETAILS

Our antennas are constructed with the best quality materials in order that the best mechanical construction can be achieved, not the cheapest and most profitable! Even a digital caliper is used (with an accuracy of .01mm) to measure the elements during production to ensure they are within 0.2mm of what they should be, ensuring they work as well as our software model predicts.

Note: Much development time has gone into our antennas, not just on basic electromagnetic design, we are able to model the effect of insulators, booms and other objects to ensure the make up of our antennas have least effect on performance and pattern degradation. More information can be found here

- · Marine grade Stainless Steel Fittings
- Original Stauff Insulation clamps
- · Mill finished boom and elements for highest levels of accuracy



**Azimuth Plot** 



**Elevation Plot** 


2 / 3



Single 6 element OP-DES up 10m above ground



2 x 6el OP-DES Yagi 3.6m apart with the bottom antenna 10m above ground



SWR



How the OP-DES looks; A 6el 10m OP-DES

Manufactured the right way, not the cheapest way!  $//\ //$ 

3 / 3